

PRT29010—Sprinter Infra-Red THERMAL PRINTER User Guide



Features

- Easy-Load paper feature
- IrDA Interface
- Rechargeable NiMH, AA batteries
- Recharge from mains
- High speed, high resolution printing capability
- Quiet, non-impact system
- Maintenance-free
- Ultra-Compact and light weight
- High reliability line head mechanism
- Low power mode
- Built in magnets so printer can be placed on vertical ferrous surface

1. PRINTER SPECIFICATIONS

Average printing speed	10 lines per second (max)	Character set	ASCII
Dimensions	85.5mm x150 mm x55 mm,	Country codes	USA, France, Germany, UK, Denmark /I/I, Sweden, Italy, Spain & Japan
Weight	Approx. 400 gms inc batteries and paper roll	Interface	
Internal power supply	4 x 1.2V NiMH 1600mAH, AA cells	IrDA	V1.0 physical layer
Paper width	58mm	Buffer size	5 Kbytes
Paper length	25m	MTBF	Approx. 10 million lines (20°C, print ratio = 25%)
Operating range	0°C to +50°C		
Storage range	-20°C to +60°C		
Charging range	+10°C to +45°C		

2. PREPARATION

2.1 Insert Batteries

We take every precaution possible to ensure your printer reaches you in perfect condition. To aid this we remove the rechargeable batteries from the unit for transit.

When you receive your printer you should be able to locate 4 x rechargeable NiMH batteries in the packaging. Remove the battery cover from the base of the printer and insert the batteries, taking care to ensure the batteries are inserted correctly using the illustration guide inside the battery compartment to guarantee the batteries are correctly positioned.

2.2 Charge Printer

Before attempting to use your new printer, you need to charge it for 16 hours using 15V centre positive charger (CHG29001). This will ensure optimum battery capacity and life.

2.3 Check Paper

Make sure a thermal paper roll is present in the paper reservoir and the leading edge emerges from the printer over the tear bar. The paper should feed from the bottom front face of the roll.

3. PRINTER OPERATION

3.1 Battery Charging

When the printer is first delivered there may be little or no charge in the printer's batteries. The printer should be **turned off**, connected to the charger (CHG29001) and allowed to charge for 16 hours before it is used for the first time.

It is recommended to connect the printer to the charger and recharge the batteries as soon as the Status LED indicates low battery (see table 4.2)

It is permissible to leave the printer permanently connected to the power adapter (CHG29001) to trickle charge the batteries. If the printer is asleep it will wake up when the adapter is connected and will not sleep while it is connected. To fast charge the batteries, the printer must be off.

If the batteries in the printer become exhausted, printing will become faint, erratic or not possible at all. **Turn off** the printer and recharge the batteries for at least 15 minutes before attempting further printing. The charger cannot supply the full power requirements for the printer during printing, so the batteries must be partially charged before printing is possible.

The printer should only be used in conjunction with the correct charger part number: CHG29001

3.2 Power On Procedure

Check the batteries are sufficiently charged. Open the paper cup lid by pulling the central lever upwards and forwards from its locked position. To avoid damage do not use excessive force. Ensure that a paper roll is present and that there are no foreign objects inside the paper reservoir. Close the lid by applying equal amounts of pressure on each side of the lid until it is in the locked position. The paper should emerge from the printer over the tear bar.

When the Status indicator is off, the printer is off. A brief press of the Mode button turns the printer on, the Status indicator will illuminate and the printer mechanism will reset. A brief press of the Mode button will turn the printer off. When the printer is asleep, pressing the Mode button will wake up the printer.

3.3 Low Power Mode

The printer incorporates two low-power modes, however the printer will not enter the low power mode if the charger is attached.

In **Sleep mode** the printer enters low power mode after a preset period of inactivity. Once asleep, the printer can be woken by sending a NULL character 1 sec before data to be printed, OR the printer can be woken by pressing the Mode button.

In **Auto Off mode** the printer cannot be woken by data transfer and must be powered-on manually.

3.4 Paper Tear Procedure

When removing printout from the printer, pull the printout toward the front of the printer and tear from one side to the other across the serrated edge.

4 PRINTER MAINTENANCE

4.1 Power On Self Test

The self test procedure will check most of the printer functions, except for the serial interface, i.e: Printer mechanism, Control circuitry, Firmware version, Print quality. When the printer is off, press and hold the Mode button depressed for approximately 2 seconds. Release the button, the printer will power on and print a self-test report.

4.2 Power Status LED (green)

The printer incorporates an LED indicator to report its condition. If there is a fault, the LED will flash in sequence. The fault can be identified by counting the number of flashes.

LED Indication	Condition	Solution
On	Printer On	-
Off	Printer Off or Asleep	-
Short flash every second	Fast Charging	-
* * *	Paper out	Fit new paper
** **	Thermal head too hot	Allow head to cool
*** **	Battery cut-out (no charge remaining)	Recharge battery
**** ****	Battery low (approx. 20% charge remaining)	Recharge battery

4.3 Charger / Busy LED (red)

LED Indication	Condition	Solution
Short flash every second when power LED is OFF	Fast Charging	-
Short flash every second when power LED is ON	Receiving data	-

4.4 Paper Out

The printer will automatically detect when the printer paper has run out, and report this using the Status LED. Use the Mode button to feed through the last few centimetres of paper and fit a new roll as described below.

4.5 Head Thermal Limit

After extensive printing the print head temperature may rise to an unusable level. The Status LED will report when this occurs, and printing will be suspended until the head temperature returns to normal levels.

4.6 Opening the Paper Cup Lid

Pull the central lever on the paper cup lid upwards and forwards until it is released from its locked position. To avoid damage do not use excessive force.

4.7 Replacing Paper Roll

If the paper roll needs replacing, open the paper cup lid and remove the spool and any remaining paper. Reel off a few centimetres from a new roll of paper. Hold approximately 5cm of paper outside the printer, place the new roll into the paper reservoir with the paper feeding from the bottom front of the roll, with the leading edge over the tear bar. Close the lid by applying equal amounts of pressure on each side of the paper cup lid until the lid is in the locked position.

5. Disposal

At the end of its working life the printer should be disposed of in accordance with The Waste Electrical and Electronic Regulations ("the WEEE Regulations), if in use within the EU, and in accordance with national requirements in other countries.

This printer contains NiMH batteries that should be disposed of by a qualified recycler or hazardous material handler.

6. ACCESSORIES

Paper Rolls

Replacement Thermal Paper Rolls	PAP26001
---------------------------------	----------

Charger

Replacement mains Charger	CHG29001
---------------------------	----------

Replacement Battery

Battery, AA 1.5V, Ni-MH (4 required)	MJ10.01
--------------------------------------	---------

Thank you for purchasing the Anton Sprinter

PRT29010 Sprinter Rev A

All instruments designed and manufactured in Great Britain. The manufacturer reserves the right to alter specifications without prior notice